

FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FOSSER Antifreeze FA 048

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

engine coolant

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Duran Lubricants & Chemicals GmbH

Street: Rodderheide 3-7 Place: D-33824 Werther

Telephone: +49 (0)5203-901510 Telefax: +49 (0)5203-901515

E-Mail: info@duran-oil.com Internet: www.fosser.de

1.4.Emergency Telephone number: Giftinformationszentrum Nord (Göttingen) - +49(0)551/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Acute Tox. 4; H302 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Ethane-1,2-diol

Signal word: Warning

Pictograms:





Hazard statements

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 2 of 13

P330 Rinse mouth.

P501 Dispose of contents / container in accordance with official regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
107-21-1	Ethane-1,2-diol			85 - 95 %	
	203-473-3	603-027-00-1	01-2119456816-28		
	Acute Tox. 4, STOT RE 2; H302 H	373			
532-32-1	Sodium benzoate	1 - < 5 %			
	208-534-8		01-2119460683-35		
	Eye Irrit. 2; H319				
1332-77-0	Dipotassium tetraborate			1 - <3 %	
	215-575-5		01-2119970730-37		
	Repr. 2; H361d				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

Specific Cor	specific Conc. Limits, M-ractors and ATE				
CAS No	EC No	No Chemical name			
	Specific Conc.	Limits, M-factors and ATE			
107-21-1	203-473-3	Ethane-1,2-diol	85 - 95 %		
	dermal: LD50	mal: LD50 = > 3500 mg/kg; oral: LD50 = 7712 mg/kg			
532-32-1	208-534-8	Sodium benzoate	1 - < 5 %		
	dermal: LD50	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3450 mg/kg			
1332-77-0	215-575-5	Dipotassium tetraborate	1 - <3 %		
		inhalation: LC50 = > 2,04 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2500 mg/kg Repr. 2; H361d: >= 5,2 - 100			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off contaminated clothing and wash it before reuse.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. Call a doctor if you feel unwell.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, consult a physician.



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 3 of 13

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth thoroughly with water.

Let water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

- alcohol resistant foam
- Extinguishing powder
- Water spray jet

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Carbon monoxide (CO)
- Carbon dioxide (CO2).
- Pyrolysis products, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin, eyes and clothes.

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 4 of 13

For containment

Stop leak if safe to do so.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Collect in closed and suitable containers for disposal.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Always close containers tightly after the removal of product.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Clear spills immediately.

Use only in well-ventilated areas.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Keep only in the original container. Store in a cool dry place.

Hints on joint storage

Do not store together with:

- Materials capable of ignition under almost all normal temperature conditions
- Explosives

7.3. Specific end use(s)

engine coolant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL



FOSSER Antifreeze FA 048

Page 5 of 13

Print date: 14.11.2022

DNEL/DMEL values

Revision date: 10.10.2022

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
107-21-1	Ethane-1,2-diol			
Worker DNEL	., long-term	inhalation	local	35 mg/m³
Worker DNEL	., long-term	dermal	systemic	106 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	local	7 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	53 mg/kg bw/day
532-32-1	Sodium benzoate			
Worker DNEL	, long-term	inhalation	systemic	3 mg/m³
Worker DNEL	., long-term	inhalation	local	0,1 mg/m³
Worker DNEL	., long-term	dermal	systemic	62,5 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	1,5 mg/m³
Consumer DN	IEL, long-term	inhalation	local	0,06 mg/m³
Consumer DNEL, long-term		dermal	systemic	31,25 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	16,6 mg/kg bw/day
1332-77-0	Dipotassium tetraborate			
Consumer DN	IEL, long-term	inhalation	systemic	3,9 mg/m³
Worker DNEL	., long-term	dermal	systemic	367,7 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	7,8 mg/m³
Worker DNEL	., acute	inhalation	systemic	7,8 mg/m³
Worker DNEL	., long-term	inhalation	local	13,6 mg/m³
Worker DNEL	., acute	inhalation	local	13,6 mg/m³
Consumer DNEL, acute		inhalation	systemic	3,9 mg/m³
Consumer DNEL, long-term		inhalation	local	13,6 mg/m³
Consumer DNEL, acute		inhalation	local	13,6 mg/m³
Consumer DNEL, long-term		dermal	systemic	185,6 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	0,92 mg/kg bw/day
Consumer DN	VEL, acute	oral	systemic	0,92 mg/kg bw/day



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 6 of 13

PNEC values

CAS No	Substance				
Environmenta	al compartment	Value			
107-21-1	107-21-1 Ethane-1,2-diol				
Freshwater	reshwater				
Freshwater (i	intermittent releases)	10 mg/l			
Marine water		1 mg/l			
Freshwater s	ediment	37 mg/kg			
Marine sedim	nent	3,7 mg/kg			
Micro-organis	sms in sewage treatment plants (STP)	199,5 mg/l			
Soil		1,53 mg/kg			
532-32-1	Sodium benzoate				
Freshwater		0,13 mg/l			
Freshwater (i	intermittent releases)	0,305 mg/l			
Marine water		0,013 mg/l			
Freshwater s	ediment	1,76 mg/kg			
Marine sedim	nent	0,176 mg/kg			
Secondary po	oisoning	300 mg/kg			
Micro-organis	sms in sewage treatment plants (STP)	10 mg/l			
Soil		0,06 mg/kg			
1332-77-0	Dipotassium tetraborate				
Freshwater					
Freshwater (intermittent releases)		13,7 mg/l			
Marine water 2					
Micro-organisms in sewage treatment plants (STP)					
Soil 5,4 mg/kg					

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat, drink, smoke, sniff. Keep away from food, drink and animal feedingstuffs.

Eye/face protection

During filling, metering, mixing and sampling must be used:

Wear eye/face protection. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 7 of 13

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374 Suitable material: NBR (Nitrile rubber) Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough

time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. EN 14605

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Combination filtering device Typ: A-P2 (EN 14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: greenish blue Odour: odourless

pH-Value: not determined

Changes in the physical state

Boiling point or initial boiling point and 160-200 °C

boiling range:

Flash point: > 120 °C

Flammability

Solid/liquid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Self-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: <0,000 01 hPa

(at 20 °C)

Density (at 15 °C): 1,127 g/cm³ Water solubility: miscible

Solubility in other solvents

Miscible with: Acetone

Partition coefficient n-octanol/water: not determined
Relative vapour density: not determined



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 8 of 13

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Avoid: Thermal decomposition

10.5. Incompatible materials

Materials to avoid:

- Oxidising agent
- Strong acid, alkalines

10.6. Hazardous decomposition products

Hazardous combustion products:

- Carbon monoxide (CO)
- Carbon dioxide (CO2).
- Pyrolysis products, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 526,3 mg/kg



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 9 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
107-21-1	Ethane-1,2-diol					
	oral	LD50 mg/kg	7712	Rat	Study report (1968)	according to BASF-internal standards
	dermal	LD50 mg/kg	> 3500	Mouse	Fundamental and Applied Toxicology 27: 1	LD50 derived from developmental toxicity
532-32-1	Sodium benzoate					
	oral	LD50 mg/kg	3450	Rat	Publication (1953)	Study predates approved guidelines. Unfa
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1974)	4 rabbits were dermally exposed
1332-77-0	Dipotassium tetrabor	ate				
	oral	LD50 mg/kg	> 2500	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1985)	other: This study was carried out to com
	inhalation (4 h) dust/mist	LC50 mg/l	> 2,04	Rat	Study report (1994)	OECD Guideline 403

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Ethane-1,2-diol)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 10 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
107-21-1	Ethane-1,2-diol						
	Acute fish toxicity	LC50 mg/l	> 72860	96 h	Pimephales promelas	Environ. Toxicology and Chemistry, Vol.	EPA 600/4-90/027. U.S. Environmental Pro
	Acute algae toxicity	ErC50 13000 mg/l	6500 -	96 h	Pseudokirchneriella subcapitata	Study report (1982)	other: EPA 600/9-78-018, 1978
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Fish toxicity	NOEC mg/l	15380	7 d	Pimephales promelas	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen
	Algae toxicity	NOEC mg/l	> 100	8 d	Scenedesmus quadricauda	REACh Registration Dossier	OECD Guideline 201
	Crustacea toxicity	NOEC 15000 mg/l	7500 -	21 d	Daphnia magna	REACh Registration Dossier	other: ASTM
532-32-1	Sodium benzoate						
	Acute fish toxicity	LC50	484 mg/l	96 h	Pimephales promelas	Vol. 2: 139-140. University of Wisconsin	EPA OPP 72-1
	Acute algae toxicity	ErC50 mg/l	> 30,5	72 h	Raphidocelis subcapitata	Study report (2010)	OECD Guideline 201
1332-77-0	Dipotassium tetraborate						
	Acute fish toxicity	LC50	74 mg/l	96 h	Limanda limanda	Publication (1985)	The acute toxicity of boron has been stu
	Acute algae toxicity	ErC50	66 mg/l	72 h	Phaeodactylum tricornutum	Study report (2011)	ISO 10253
	Acute crustacea toxicity	EC50	133 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem., 3, #1, 89-94 (1	other: ASTM Standard E 729-80
	Fish toxicity	NOEC	5,6 mg/l	34 d	Danio rerio	Study report (2000)	OECD Guideline 210
	Algae toxicity	NOEC mg/l	>= 100	10 d	Agmenellum quadruplicatum	J. Fish. Res. Board Can., 32, #12, 2487-	Axenic cultures of 19 species were chose
	Crustacea toxicity	NOEC mg/l	33,1	28 d	Americamysis bahia	Study report (2011)	EPA OPPTS 850.1350
	Acute bacteria toxicity	(EC50 mg/l)	> 175	3 h	Activated sludge	Study report (2000)	OECD Guideline 209

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.



	FOSSER Antifreeze FA 048	
Revision date: 10.10.2022		Page 11 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-21-1	Ethane-1,2-diol	-1,36
532-32-1	Sodium benzoate	1,88

BCF

CAS No	Chemical name	BCF	Species	Source
1332-77-0	Dipotassium tetraborate	0,558	Oncorhynchus nerka	Water Research Vol.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 12 of 13

14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC): 99,99 % (1126,887 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

Print date: 14.11.2022

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



FOSSER Antifreeze FA 048

Revision date: 10.10.2022 Page 13 of 13

Classification for mixtures and used evaluation method according to GB CLP Regulation

	<u> </u>
Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)