

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 1 of 19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FOSSER Gear Ultra DCT F-LV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

gear oil

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Duran Lubricants & Chemicals GmbH
Street: Rodderheide 3-7
Place: D-33824 Werther
Telephone: +49 (0)5203-901510
e-mail: info@duran-oil.com
Internet: www.fosser.de
Responsible Department: Produktsicherheit / Product Safety
info@duran-oil.com

Fax: +49 (0)5203-901515

1.4. Emergency telephone number:

Gifteinformationszentrum Nord
(Göttingen)+49 (0)551/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Phenol, C14-18-alkyl derivs
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
maleic anhydride
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 2 of 19

protection.

P302+P352

IF ON SKIN: Wash with plenty of Water and soap.

P362+P364

Take off contaminated clothing and wash it before reuse.

P501

Dispose of contents / container in accordance with official regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 3 of 19

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			33 - <= 56,3 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified			18 - < 31,25 %
	276-738-4	649-483-00-5	01-2119474889-13	
	Asp. Tox. 1; H304			
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			0 - < 1,05 %
	406-040-9	607-530-00-7	01-0000015551-76	
	Aquatic Chronic 4; H413			
36878-20-3	Bis(nonylphenyl)amine			0 - < 1,05 %
	253-249-4		01-2119488911-28	
	Aquatic Chronic 4; H413			
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			0 - < 1,05 %
	276-737-9	649-482-00-X	01-2119474878-16	
	Asp. Tox. 1; H304			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			0 - < 1,05 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
	Alkyl phosphites			0 - < 0,53 %
	424-820-7		01-0000017126-75	
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 1; H312 H314 H400 H410			
	N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine			0 - < 0,27 %
	930-859-5		01-0000015551-76	
	Skin Corr. 1C, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			
1190625-94-5	Phenol, C14-18-alkyl derivs			0 - < 0,11 %
	813-078-3		01-2119498288-19	
	Skin Sens. 1B, STOT RE 2; H317 H373			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			0 - <= 0,029997 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
108-31-6	maleic anhydride			0 - <= 0,01049 %
	203-571-6	607-096-00-9		
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314 H318 H334 H317 H372 EUH071			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 4 of 19

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
		Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	33 - <= 56,3 %	
		inhalation: LC50 = 5,53 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
72623-87-1	276-738-4	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified	18 - < 31,25 %	
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
125643-61-0	406-040-9	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	0 - < 1,05 %	
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
36878-20-3	253-249-4	Bis(nonylphenyl)amine	0 - < 1,05 %	
		oral: LD50 = > 5000 mg/kg		
72623-86-0	276-737-9	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified	0 - < 1,05 %	
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	0 - < 1,05 %	
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
	424-820-7	Alkyl phosphites	0 - < 0,53 %	
		dermal: LD50 = > 500 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		
	930-859-5	N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine	0 - < 0,27 %	
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
108-31-6	203-571-6	maleic anhydride	0 - <= 0,01049 %	
		dermal: LD50 = 2620 mg/kg; oral: LD50 = 400 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100		

Further Information

This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

Do not leave affected person unattended.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. Call a doctor if you feel unwell.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 5 of 19

ophthalmologist. After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Rinse mouth thoroughly with water.

Let water be drunk in little sips (dilution effect).

Do NOT induce vomiting.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers.

- alcohol resistant foam.
- Carbon dioxide (CO₂).
- Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable. Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Carbon monoxide (CO)
- Carbon dioxide (CO₂).
- Nitrogen oxides (NO_x)
- Pyrolysis products, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Keep people at a distance and stay on the windward side.
Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear protective gloves/protective clothing and eye/face protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 6 of 19

Do not allow to enter into soil/subsoil.
Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.
Remove from the water surface (e.g. skimming, sucking).

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of oil dust.
Use personal protection equipment.
Do not put any product-impregnated cleaning rags into your trouser pockets.
Clear spills immediately.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep container tightly closed and in a well-ventilated place.
Keep only in the original container. Store in a cool dry place. (Protect from moisture.)
Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

Do not store together with:
- Materials capable of ignition under almost all normal temperature conditions
- Explosives

7.3. Specific end use(s)

gear oil

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-31-6	Maleic anhydride	-	1		TWA (8 h)	WEL
		-	3		STEL (15 min)	
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 7 of 19

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³	
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³	
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate			
Worker DNEL, long-term	dermal	systemic	1,67 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	1,62 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,93 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	6,6 mg/m ³	
36878-20-3	Bis(nonylphenyl)amine			
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³	
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 8 of 19

Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Alkyl phosphites			
Worker DNEL, long-term	inhalation	systemic	1,76 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,43 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine			
Worker DNEL, long-term	inhalation	systemic	2,93 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,72 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,42 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,42 mg/kg bw/day

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 9 of 19

PNEC values

CAS No	Substance	
	Environmental compartment	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
	Freshwater	0,018 mg/l
	Freshwater (intermittent releases)	0,018 mg/l
	Marine water	0,002 mg/l
	Freshwater sediment	2 mg/kg
	Marine sediment	0,2 mg/kg
	Secondary poisoning	41,33 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	10 mg/kg
36878-20-3	Bis(nonylphenyl)amine	
	Freshwater	0,412 mg/l
	Freshwater (intermittent releases)	1 mg/l
	Marine water	0,041 mg/l
	Freshwater sediment	1 mg/kg
	Marine sediment	0,1 mg/kg
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
	Alkyl phosphites	
	Freshwater	0,0009 mg/l
	Freshwater (intermittent releases)	0,0009 mg/l
	Marine water	0,00009 mg/l
	Freshwater sediment	0,73 mg/kg
	Marine sediment	0,073 mg/kg
	Secondary poisoning	10 mg/kg
	Micro-organisms in sewage treatment plants (STP)	5 mg/l
	Soil	0,086 mg/kg
	N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine	
	Freshwater	0,001 mg/l
	Freshwater (intermittent releases)	0,008 mg/l
	Marine water	0 mg/l
	Freshwater sediment	0,004 mg/kg

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 10 of 19

Marine sediment	0 mg/kg
Secondary poisoning	16,67 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	0,002 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Take off contaminated clothing and wash it before reuse.
Wash hands before breaks and after work.
When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye/face protection. During filling, metering, mixing and sampling must be used:
EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended glove articles: EN ISO 374

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough time: > 8h

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellow
Odour:	not determined
Odour threshold:	not determined
pH-Value:	not determined

Changes in the physical state

Melting point/freezing point: -51 °C

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 11 of 19

Boiling point or initial boiling point and
boiling range: not determined

Flash point: 216 °C

Flammability

Solid/liquid: not determined

Explosive properties

The product is not: Explosive. Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Lower explosion limits: not determined

Upper explosion limits: not determined

Auto-ignition temperature: not determined

Decomposition temperature: not determined

Oxidizing properties

The product is not: oxidising.

Vapour pressure: not determined

Density (at 15 °C): 0,84 g/cm³

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Viscosity / kinematic: 25 mm²/s
(at 40 °C)

Relative vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

10.4. Conditions to avoid

Avoid: Thermal decomposition

10.5. Incompatible materials

Materials to avoid:

- Oxidising agent
- Reducing agent
- Acids

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 12 of 19

10.6. Hazardous decomposition products

Hazardous combustion products:

- Carbon monoxide (CO)
- Carbon dioxide (CO₂).
- Nitrogen oxides (NO_x)
- Pyrolysis products, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 13 of 19

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000 Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000 Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50	5,53 mg/l Rat		OECD Guideline 403
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000 Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000 Rabbit	Study report (1982)	OECD Guideline 402
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate				
	oral	LD50 mg/kg	> 2000 Rat	Study report (2005)	OECD Guideline 423
	dermal	LD50 mg/kg	> 2000 Rat	Study report (2000)	OECD Guideline 402
36878-20-3	BIs(nonylphenyl)amine				
	oral	LD50 mg/kg	> 5000 Rat	Study report (1981)	OECD Guideline 401
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000 Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000 Rabbit	Study report (1982)	OECD Guideline 402
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg	> 5000 Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000 Rabbit	Study report (1982)	OECD Guideline 402
	Alkyl phosphites				
	oral	LD50 mg/kg	> 2000 Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 mg/kg	> 500 Rabbit	Study report (1996)	OECD Guideline 402
	N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine				
	oral	LD50 mg/kg	> 2000 Rat	Study report (1995)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000 Rabbit	Study report (1993)	OECD Guideline 402
108-31-6	maleic anhydride				
	oral	LD50 mg/kg	400 Rat	GESTIS	
	dermal	LD50 mg/kg	2620 Rabbit	GESTIS	

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 14 of 19

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Phenol, C14-18-alkyl derivs; methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; maleic anhydride)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

See section 12.6

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The component reaction product of alkylthioalcohol and a substituted phosphorus compound (EC 424-820-7) is part of a mixture of substances that was tested for its effects on aquatic organisms in acute and chronic water tests. The test results show no ecotoxicological effects. Conclusion by analogy

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 15 of 19

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil - unspecified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate					
	Acute fish toxicity	LC50 mg/l	> 0,001	96 h	Oncorhynchus mykiss	Study report (2009)
	Acute algae toxicity	ErC50 mg/l	> 0 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)
	Acute crustacea toxicity	EL50 mg/l	110 mg/l	48 h	Daphnia magna	Study report (2000)
	Fish toxicity	NOEC mg/l	0,36	33 d	Pimephales promelas	Study report (2009)
	Crustacea toxicity	NOEC mg/l	3,2 mg/l	21 d	Daphnia magna	Study report (2010)
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	activated sludge of a predominantly domestic sewage	Study report (2000)
36878-20-3	Bis(nonylphenyl)amine					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Danio rerio (zebrafish)	ECHA Dossier
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	Study report (2019)
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2004)
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil - unspecified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)
	Alkyl phosphites					
	Acute fish toxicity	LC50	1,5 mg/l	96 h		

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 16 of 19

	Acute algae toxicity	ErC50 mg/l	0,31	72 h	Raphidocelis subcapitata	Study report (1996)	EU Method C.3
	Acute crustacea toxicity	EL50 mg/l	0,09	48 h	Daphnia magna	Study report (1996)	EU Method C.2
	Crustacea toxicity	NOEC mg/l	0,14	21 d	Daphnia magna	Study report (2001)	OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	> 50	3 h	Activated sludge	Study report (1996)	OECD Guideline 209
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine							
	Acute fish toxicity	LC50 mg/l	690 mg/l	96 h	Cyprinodon variegatus	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,79	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 4 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209
108-31-6	maleic anhydride						
	Acute algae toxicity	ErC50 mg/l	29 mg/l	72 h	Desmodesmus subspicatus	IUCLID	

12.2. Persistence and degradability

Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
36878-20-3	BIs(nonylphenyl)amine	7,6
	N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine	5,2

BCF

CAS No	Chemical name	BCF	Species	Source
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3- (3,5-di-tert-butyl-4-hydroxyphenyl)propi onate	38	Cyprinus carpio	Study report (2002)
36878-20-3	BIs(nonylphenyl)amine	1584,89	Cyprinus carpio	Study report (2000)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 17 of 19

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 18 of 19

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

Directive 2010/75/EU on industrial emissions: 0,01 % (0,088 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 0,01 % (0,088 g/l)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

Safety Data Sheet

FOSSER Gear Ultra DCT F-LV

Revision date: 22.04.2025

Page 19 of 19

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

EC/EEC: European Community/European Economic Community

EU: European Union

M-factor: Multiplying factor

IATA: International Air Transport Association

DGR: Dangerous Goods Regulations

ICAO: International Civil Aviation Organization

TI: Technical Instructions

VOC: volatile organic compound

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)